

HUNTER PENROSE

Hunter Penrose Supplies Ltd
11 Curve Serviced Offices, 30B Wild's Rents, London, SE1 4QG
0203 751 1101
Warehouse: Unit 7, The Bell Centre, Newton Road, Crawley, West Sussex, RH10 9FZ
01293 515575
 e-mail: info@hunterpenrose.co.uk
www.hunterpenrose.co.uk

equipment data sheet

equipment type

model ref: SL range of film processors

Description

1. SL film processors, with wide film-input boxes, are compatible with any type of film setter.
3. The SL film processors' simple and stable full-function micro-computer reinforces the superior quality of SL film processor.
4. SL Processors feature user-friendly operation,
5. Micro computer display, figures being clear at a glance. Accurate and convenient menu figure setting and modification. Easy to remove components make cleaning and maintenance simple.
6. Chemical saving and processing features are standard. A SL film path ensures no scartching film jams.
7. Automatic developer and fixer replenishment. Automatic washing and drying stand-by after film-processing completed.
8. SL film processors use a stainless steel frame to ensure no corrosion during working life with refined stainless steel tank that is firm, durable and high-quality rollers that are wear-, corrosion-, ageing- and heat-resistant.



Specification:

Model	SL-200H	SL-250H	SL-280H	SL-320H	SL-370H	SL-450H	SL-500H
Roller Width	533	660	738	840	965	1186	1295
Film Size (min)	50 X 100						
Tank, dev	11	13	15	17	20	25	28
Tank, fix	11	13	15	17	20	25	28
Tank, wash	11	13	15	17	20	25	28
Film Process	Dev 310 mm, Fixation 310 mm, Wash 310 mm, Dry 250 mm						
Processing Speed	50-200 cm/min						
Replenishment	Manual/ automatic						
Dev Time	20-60 seconds						
Chemical Temperature	20-45 °C						
Dry Temperature	20-70 °C						
Power Supply	220 V ±10% 50/60 Hz 15A						
Net Weight (kg)	145	160	180	200	220	260	290